

# Volcano Detection without Ground Truth

Padhraic Smyth\*, Usama Fayyad

Jet Propulsion Laboratory MS 238-420,  
California Institute of Technology, 4800 Oak Grove Drive Pasadena, CA 91109

Michael Burl, Pietro Perona

EE Dept., California Institute of Technology 116-81, Pasadena, CA 91125

## Abstract

Manual detection and characterization of small geological objects in remotely sensed imagery can be a time-consuming and tedious task for planetary geologists. For example, in the recently acquired 30,000 synthetic-aperture radar images from the Magellan mission to Venus, there are estimated to be on the order of  $10^5$  to  $10^6$  small volcanoes visible in the data [1]. In this paper we describe the development of a pattern recognition system which aims to automate the low-level task of volcano detection. In particular, we focus on the problems posed by the lack of absolute ground-truth.

The overall pattern recognition system consists of focus of attention via matched filtering, feature generation from local regions of interest (ROIs) via the use of singular-value decomposition filters, and subsequent discrimination of ROIs into volcano and non-volcano categories via standard classification models [2]. In order to provide **training data** for the system, planetary **geologists** familiar with Venusian volcanism identify the likely locations of volcanoes in particular training images. The geologists assign to each candidate volcano a predetermined level of certainty, which is in turn mapped to a subjectively determined posterior probability value. Quantization helps calibration by anchoring the subjective estimates to specific predefined **qualitative** categories. The probabilistic estimates are useful in two respects. Firstly they can be used during the training/estimation process (as described [3]): fractions of training exemplars are assigned to each class according to the subjective probability estimate associated with that class. Secondly, the probabilistic estimates can be directly used for performance assessment of both algorithms and humans relative to the reference consensus (we use consensus-derived estimates **as our** reference and use individually-derived estimates to calibrate individual **scientist** performance). Probabilistic labels lead **naturally** to the notion of *probabilistic ROC* curves - we describe their use and interpretation. While different geologists operate at different points along the overall curve in terms of absolute discrimination (corresponding to different utility functions), their estimated probabilistic ROC performance is quite similar. Empirical results thus far indicate that the current algorithmic system is close to the performance of geologists on high resolution images in terms of detection, but is relatively weak in terms of its ability to provide **accurate** probabilistic estimates. We discuss the strengths and weaknesses of the current approach and describe ongoing work and future directions of the research.

## References

1. J. E. Guest et al., 'Small volcanic edifices in the plains of Venus,' *Journal of Geophysical Research*, vol. 97, no. E10, pp. 15949-15966, October 25, 1992.
2. M. C. Burl et al., 'Automating the hunt for volcanoes on Venus,' CNS Technical Report 34, Computation and Neural Systems Dept., California Institute of Technology, December 15th, 1993.
3. P. Smyth, 'Learning with probabilistic supervision,' in *Computational Learning Theory and Natural Learning Systems 3*, T. Petsche, M. Kearns, S. Hanson, R. Rivest (eds), Cambridge, MA: MIT Press, in press.

Topic: Applications

Presentation: Poster

---

\* Author to whom correspondence should be addressed, [pjs@galway.jpl.nasa.gov](mailto:pjs@galway.jpl.nasa.gov). The research described in this paper was performed at the Jet Propulsion Laboratory, California Institute of Technology, under a contract with the National Aeronautics and Space Administration and was supported in part by ARLA under **grant** number N00014-92-J-1860.